

# Images

Every business can find dozens of practical uses for the world's first Still Video Camera. Full-color images are captured electronically on a wafer-size, erasable Video Floppy—up to 50 per disk. No film, no waste, no waiting. With XAP SHOT's built-in playback function you can show images immediately on any TV or monitor. It's the Still Video camera of the future, ready to work for you today.





## Go to Work





Realtors • Insurance Agents • Talent Scouts • Claims Adjustors • Private Investigators • Location Hunters • Civic Planners • Zoo Curators • Fire Inspectors • Health Officials • Archaeologists • Agricultral Agents • Aerobics Instructors • Opinion Pollsters • Event Planners...



### Convince

Presenting your ideas visually is quick and easy with XAP SHOT. Business meetings, over-the-counter sales talks, point-of-purchase displays-all benefit from the convenience and cost-effective simplicity of Canon XAP SHOT.



SHOW & SELL

Travel Agencies • Car Rentals & Used Car Lots • Ad Agencies • Fund Raisers • Hair Stylists • Art Galleries • Jewelers • Boutiques & Department Stores • Hotel Information Desks • Sportfishing Charters • Bankers • Air & Bus Terminals • Housing Directories...

### **APPLICATIONS UNLIMITED**

### Record, Play and Erase

What you do with this epoch-making camera is your business. Ours was making sure you can do it faster, cheaper and better. Everything that can be automatic is automatic in this ultra-compact SV camera, including **Auto-Exposure**, the **Built-In Flash** and **Auto White Balance**. And remember, XAP SHOT works on *any* TV or monitor of the NTSC type (the kind used everywhere in the U.S.). Direct input to a monitor-type Video terminal or RF connection to a TV's antenna takes only seconds.

### **Special Features**

XAP SHOT has a Continuous-Shooting Mode (up to three shots per sec.), Insert Shooting to let you erase and reshoot any image, any time, and useful finishing touches such as Exposure Compensation, Macro Capability, a Self-Timer, Optional Teleconverter and more.

### **Technical Triumphs in Still Video**

Canon R&D has produced a single-chip, **Pure-Color Stripe Filter** and other SV breakthroughs to keep camera size small and picture quality sensational. The 1/2-inch **CCD Image Sensor** that instantly converts light to electrical impulses is the high-density type, with 786 pixels (horiz.). Other special circuits keep video "noise" in check, and the **High-Band System** boosts the picture quality far above ordinary video cameras to assure a bright, sharp and natural picture, even on a big-screen TV or monitor.

### **ERGONOMIC DESIGN**



### **GET DOWN TO BUSINESS**

Load the Video Floppy as you would a cassette, snap down the cover and XAP SHOT is ready for the job. The camera automatically chooses a blank track for you, or you can use any other. The LCD (liquid crystal display) panel shows the track number, battery condition, single/continuous-shot modes, self-timer status, while LEDs inside the viewfinder indicate field masking for macrophotography, flash charging, low-luminance interlock range.



XAP SHOT (White)





### Accessories

### RC-250 Kit



### **Action Set** AS-C25



Action Grip AG-C25 Teleconverter TC-C2513

- XAP SHOT (RC-250)
- Video Floppy Disk VF-50 Battery Pack BP-4P
- Battery Charger BA-24P AC Coupler AV-C25 Pin Cable KE-PIN
- Mini-Plug Pin Cable KE-M2P Soft Case SC-C25

### Wriststrap WS-C25

### SHOOTING







Video Floppy Disk VF-50

### **PLAYING**





**POWER** 







### **Specifications**

Type

Electronic lens-shutter camera

Image Pickup Device

1/2-inch CCD (786 pixels horizontally)

Recording/Playback System

Field mode; Conforms to the High-Band format agreed upon by the Electronic Still Camera

Standardization Committee

Video Signal

NTSC color format

**Recording Medium** 

Still Video floppy disk

Built-in, fixed-focus type with macro mechanism for extreme close-ups at 12in.

Focal Length/Aperture

11mm (equivalent to 60mm on 35mm cameras), f/2.8 **Shooting Distance Range** 

3.3 ft. (1 m) to infinity [12 in. (30 cm) from CCD image pickup surface in macrophotography)

Viewfinder

Real-image secondary imaging finder Magnification: 0.55X

Finder Coverage: 84%

Dioptric Adjustment: -4 diopter to +2 diopter

Light Metering System

Feedback AE with external photometric sensor and CCD signal

Exposure Mode

NOTES:

CANADA

Program AE (1/30 sec., f/2.8 to 1/500 sec., f/22)

Metering Range EV 8 to EV 18 (equivalent to ISO 100)

**Exposure Compensation** 

+ 1.5 EV (via exposure compensation button)

White Balance

Automatic tracking system

**Shooting Mode** 

Single-image and continuous (3 images/sec.)

Shooting

Self-time

10-second delay

Flash

Built-in, light-amount adjusting type

AUTO (at EV 8 or below)/ON/OFF

Flash-coupling Range

Within approx. 10 ft. (3m)

Video Output

1Vp-p, 75Ω, unbalanced (2.5mmφ mini-jack)

Horizontal Resolution

Recording/Playback: 300 TV lines

Playback: 400 TV lines Playback Function

Playback single image or continuous images (approx. 4 images/sec.) by means of Forward or Reverse buttons; playback automatically cancelled when single-image display exceeds 2 minutes (when using battery pack) or 15 minutes (when using Battery

Charger/AC Coupler). **Erasure Function** Single-image erasure

• This camera conforms to the High-Band format agreed upon by the Electronic Still Camera Standardization Committee.

Please note that video floppy disks recorded in High-Band can only be played back on the player bearing the mark HiVF In playback of video floppy disks not recorded in High-Band, correct image reproduction might not be available.

LCD Panel

7-segment, 2-digit LED alphanumeric and mark lighting or blinking for track number, shooting mode, disk condition, battery condition, error

Viewfinder Information

LED grows for flash-charging completed or blinks for out of the low-luminance interlocking range, flash charging,: warning; macrophotography

Disk Initialization

Normal Mode: Head automatically set to the empty track next to last (highest number) recorded track. Insert Mode: Head manually set to a recordable track with Forward/Reverse buttons.

**Power Source** 

One Battery Pack BP-4P (exclusive lead-acid battery, 8V, 200mAh)

**Battery Life** 

Recording: Approx. 800 images without flash use Approx. 200 ~ 300 images with 25% flash use (at 20°C with new fully charged Battery Pack)

Playback: Approx. 10~15 minutes (at 20°C with new fully charged Battery Pack)

Tripod Socket

Provided on the optional Action Grip AG-C25

External Color

Milky white or black Dimensions (W $\times$ H $\times$ D)

 $5-9/16 \times 1-3/8 \times 4-3/16$  in.  $(142 \times 34.5 \times 106$  mm)

Weight 14-11/16 oz. (420 g) body only

\* All data are based on Canon's Standard Test Method.

\*Subject to change without notice.



Enjoy easy extended payments with the Canon Credit Card Ask for details at participating Canon dealers and retailers Available only in U.S.

Canon is a registered trademark of Canon Inc.

CANON U.S.A., INC. HEADQUARTERS

Images on TV monitors and examples in this catalog are simulated.

Please use video floppy disks of the worldwide standard for shooting and recording.

STILL VIDEO PRODUCTS GROUP TAMAGAWA PLANT 770, Shimonoge, Takatsu-ku, Kawasake-shi, Kanagawa 213, Japan

CANON U.S.A., INC. SERVICE DIVISION CANON U.S.A., INC. ATLANTA OFFICE CANON U.S.A., INC. CHICAGO OFFICE CANON U.S.A., INC. LOS ANGELES OFFICE CANON U.S.A., INC. SANTA CLARA BRACH CANON U.S.A., INC. DALLAS OFFICE

CANON U.S.A., INC. WASHINGTON D.C. BRANCH CANON U.S.A., INC. HONOLULU BRANCH

CANON CANADA INC. HEADQUARTERS CANON CANADA INC. MONTREAL SERVICE CENTRE CANON CANADA INC. CALGARY OFFICE

CENTRAL &	
COLITIL AMEDICA	

CANON LATIN AMERICA, INC. DEPTO. DE VENTAS

CANON LATIN AMERICA, INC. CENTRO DE SERVICIO Y REPARACION

CANON LATIONOAMERICA DE MEXICO, S.A. DE C.V.  Montecto No.11 P.B. Col. Napoles C.P. 03810 Mexico, D.F.		
	Montecito No.11 P.B. Col. Napoles C.P. 03810 Mexico.	

PUB. J-CE-3036A © CANON INC. 1989 1089SY50

PRINTED IN JAPAN